



## NEODYMIUM SERIES

# KAPPALITE™ 3010LF-4

High power subwoofer recommended for vented and horn loaded enclosures.



- |                                   |   |  |  |
|-----------------------------------|---|--|--|
| <input type="checkbox"/> Midrange | <input checked="" type="checkbox"/> Woofer      | <input type="checkbox"/> Sealed Box            | <input type="checkbox"/> Scoop Loading           |
| <input type="checkbox"/> Midbass  | <input checked="" type="checkbox"/> Subwoofer   | <input checked="" type="checkbox"/> Vented Box | <input checked="" type="checkbox"/> Horn Loading |
|                                   | <input checked="" type="checkbox"/> Bass Guitar |  |  |

### SPECIFICATION

Nominal Basket Diameter	10", 254 mm
Nominal Impedance*	4 Ω
Power Rating**	
Watts	550 W
Music Program	1100 W
Resonance	40 Hz
Usable Frequency Range	42 Hz – 1.4 kHz
Sensitivity***	91.6 dB
Magnet Weight	11 oz.
Gap Height	0.365", 9.3 mm
Voice Coil Diameter	3", 76 mm

### THIELE & SMALL PARAMETERS\*

Fs	40 Hz
Re	3.78 Ω
Le	0.62 mH
Qms	7.09
Qes	0.26
Qts	0.25
Vas	1.89 cu.ft., 53.5 liters
Vd	305.4 cc
Cms	0.3 mm/N
BL	13.89 T-M
Mms	53 grams
EBP	153
Xmax	8.52 mm
Sd	358.4 cm <sup>2</sup>
Xlim	15.7 mm

### MOUNTING INFORMATION


Recommended Enclosure Volume	
Sealed	N/A
Vented	19.82–84.95 liters, 0.7–3 cu.ft.
Driver Volume Displaced	0.037 cu.ft., 1.06 liters
Major Diameter	11.18", 284 mm
Flat to Flat Diameter	10", 254 mm
Baffle Hole Diameter	9.12", 231.7 mm
Front Sealing Gasket	Yes
Rear Sealing Gasket	Yes
Mounting Holes Diameter	0.29", 7.4 mm
Mounting Holes B.C.D.	10.49", 266.5 mm
Depth	5", 127 mm
Net Weight	7.6 lbs , 3.45 kg
Shipping Weight	9.2 lbs , 4.17 kg

### MATERIALS OF CONSTRUCTION

- \_\_\_\_\_ Copper voice coil
- \_\_\_\_\_ Polyimide former
- \_\_\_\_\_ Neodymium magnet
- \_\_\_\_\_ Vented core
- \_\_\_\_\_ Die-cast aluminum basket
- \_\_\_\_\_ Treated paper cone
- \_\_\_\_\_ Sealed cloth Edge
- \_\_\_\_\_ Treated paper dust cap



### FREQUENCY RESPONSE & IMPEDANCE CURVE\*





*From design and manufacturing to the stage or studio. Once you've experienced the performance of Eminence, you'll never accept anything else.*

## MISSION STATEMENT

*Eminence is dedicated to providing the best Quality, Value and Service to meet our customers' needs.*

## FOOTNOTES

- \* Please consult [www.eminence.com](http://www.eminence.com) for specifications of models with alternative impedances.
- \*\* Multiple units exceed published ratings evaluated under EIA 426A specification while tested in a free-air, non-temperature-controlled environment.
- \*\*\* The average output across the usable frequency range when applying 1W/1m into the nominal impedance. i.e: 2.83V/8Ω, 4V/16Ω. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2 ft. x 2 ft. baffle is built into the wall with the speaker mounted flush against a steel ring for minimum diffraction | Carver PM-120 amplifier | 2700 cu. ft. chamber with fiberglass on all six surfaces (three with custom-made wedges).
- \*\*\*\* BETA 8CX, 10CX, and 12CX are coaxial speakers with tweeter sold separately. Published usable frequency response contingent upon use of ASD:1001 HF Driver.
- \*\*\*\*\* Multiple units exceeded published ratings evaluated under EIA-426A or AES specification while mounted on Eminence's H290, H290S, or H2EA horn in a non-temperature-controlled environment.
- \*\*\*\*\*The average on axis output across the entire usable frequency range when applying 1W/1m into the nominal impedance, i.e. 2.83V/8Ω, 4V/16Ω. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2ft x 2ft baffle is built into the wall with horn front mounted | Carver PM-120 amplifier | 2700 cu.ft. chamber with fiberglass on all six surfaces (three with custom-made wedges).

Prices, specifications and product cosmetics are subject to change without notice.

