

COMPRESSION DRIVERS



N151M-8

- SCREW-ON
 BOLT-ON

SPECIFICATION

Throat Size	1.0", 25.4 mm
Nominal Impedance*	8 Ω
Minimum Impedance	5.2 ohm @ 6.2 kHz
Power Rating*	45 W (AES)
Resonance	1.24 kHz
DC Resistance (Re)	4.1 Ω
Usable Frequency Range	1.8 kHz - 27 kHz
Recommended Crossover	1.8 kHz / 12 dB
Sensitivity*	111.5 dB
Magnet Material	Neodymium
Magnet Weight	4.5 oz, 0.13 kg
Voice Coil Diameter	1.5", 38.1 mm
Voice Coil Former	Polyimide
Diaphragm Material	Mylar

MOUNTING INFORMATION

Overall Diameter	3.6", 91.4 mm
Driver Volume Displaced	0.005 cu.ft., 0.14 liters
Depth	1.23", 31.2 mm
Net Weight	1.70 lbs., 0.77 kg
Shipping Weight	1.8 lbs., 0.82 kg
Mounting Thread	N/A
Mounting Holes Diameter	2X 1/4-20
Mounting Holes B.C.D.	3.00", 76.2 mm

FREQUENCY RESPONSE & IMPEDANCE CURVE*

