



SPX-31M

Order No.: 10.1660

Price upon request

PRODUCTINFOS

Hi-fi full range speaker, 20 W, 8 Ω

- Excellent sound quality
- High-quality paper cone
- Aluminium phase plug for optimising radiation pattern
- Rear-ventilated centering spider
- Magnet system with shielding
- Application in small speakers or satellite systems
- Ideally suited for application in FAST speakers (full range and subwoofer technology)

HOBBY HiFi 06/2015

"Ideally suited as a desktop speaker system.
Very neat workmanship."

TECHNICAL SPECIFICATIONS

SPX-31M

Impedance (Z)	8 Ω
Frequency range	f3-20,000 Hz
Resonant frequency (fs)	110 Hz
Power rating	20 W
Peak music power output	40 W
Sensitivity	86 dB/W/m
Suspension compl. (Cms)	0.92 mm/N
Moving mass (Mms)	1.9 g
Mech. Q factor (Qms)	3.707
Electr. Q factor (Qes)	0.69
Total Q factor (Qts)	0.58
Equivalent volume (Vas)	1.32 l
DC resistance (Re)	6.4 Ω
Force factor (BxL)	3.64 Tm
Voice coil induct. (Le)	0.18 mH
Voice coil diameter	\varnothing 20 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	\pm 1.1 mm
Eff. cone area (Sd)	32 cm ²
Magnet weight	119 g
Magnet diameter	\varnothing 68 mm
Mounting cutout	\varnothing 71 mm
Mounting depth	53 mm
Dimensions	\varnothing 93 mm x 55 mm
Outside diameter	\varnothing 93 mm
Width	\varnothing 93 mm
Depth	55 mm
Admiss. ambient temp.	0-40 °C
Weight	0.49 kg
Sales unit	1
Type of speaker	3"