National Semiconductor

ADVANCE INFORMATION

LMC6772 Dual, LMC6774 Quad, Micro-Power Rail-To-Rail Input and Open Drain Output CMOS Comparator

General Description

The LMC6772/4 is an ultra low power dual/quad comparator with a maximum 10 μA/comparator power supply current. It is designed to operate over a wide range of supply voltages, from 2.7V to 15V. The LMC6772/4 has guaranteed specs at 2.7V to meet the demands of 3V digital systems.

The LMC6772/4 has an input common-mode voltage range which exceeds both rails. This is a significant advantage in low-voltage applications. The LMC6772/4 also features an open-drain output. This architecture is ideal for mixed supply voltage systems as an external resistor can be used to pull the output up to + 15V, regardless of the supply voltage.

A quiescent power consumption of 50 μ W/Amplifier (@Vs = 5V) makes the LMC6772/4 ideal for applications in portable phones and hand-held electronics. The ultra-low supply current is also independent of the power supply voltage. Guaranteed operation at 2.7V and rail-to-rail performance make the device ideal for battery-powered applications.

Features (Typical unless otherwise noted)


- Low power consumption
- $I_S = 10 \,\mu\text{A/comp}$
- Wide range of supply voltages
- 2.7V to 15V
- Rail-to-Rail Input Common Mode Voltage Range
- Open-drain output stage
- Short circuit protection

- 40 mA
- Short circuit protection
- Propagation delay (@V_S = 5V, 100 mV overdrive) 5 μ s
- Refer to the LMC6762/4 datasheet for a device with similar specs and a push-pull output stage

Applications

- Laptop computers
- Mobile Phones
- Metering systems
- Hand-held electronics
- RC timers, Window Comparators, Multivibrators
- Alarm and monitoring circuits

Connection Diagrams



Top View

OUT B 2 OUT A 2 V 3 IN A 5 IN B 6 IN B 7

Top View

14-Pin DIP/SO

TL/H/12347-2

13 OUT D 12 V

Package	Temperature Range Industrial,40°C to +85°C	NSC Drawing	Transport Media
8-Pin Molded DIP	LMC6772AIN, LMC6772BIN	N08E	Rails
8-Pin Small Outline	LMC6772AIM, LMC6772BIM	MOBA	Rails
	LMC6772AIMX, LMC6772BIMX		Tape and Reel
14-Pin Molded DIP	LMC6774AIN, LMC6774BIN	. N14A	Rails
14-Pin Small Outline	LMC6774AIM, LMC6774BIM	M14A	Rails
	LMC6774AIMX, LMC6774BIMX		Tape and Reel

TL/H/12347-1