


MM5Z2V4 - MM5Z75V

Zener Diodes


Features

- Wide Zener Voltage Range Selection, 2.4V to 75V
- Flat Lead, Surface Mount Device Under 0.70mm Height
- Extremely Small Outline Plastic Package SOD523F
- Moisture Sensitivity Level 1
- Pb Free Version and RoHS Compliant
- Matte Tin(Sn) Lead Finish
- Band Indicates Cathode
- Green Mold Compound



SOD-523F

Electrical Symbol



Absolute Maximum Ratings $T_a = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Value | Units |
|-----------|-----------------------------|-------------|------------------|
| P_D | Power Dissipation | 200 | mW |
| T_{STG} | Storage Temperature Range | -55 to +150 | $^\circ\text{C}$ |
| T_{OPR} | Operating Temperature Range | -55 to +150 | $^\circ\text{C}$ |

* These ratings are limiting values above which the serviceability of the diode may be impaired.

Thermal Characteristics

| Symbol | Parameter | Value | Unit |
|-----------------|---|-------|--------------------|
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient | 500 | $^\circ\text{C/W}$ |

* Device mounted on FR-4 PCB minimum land pad.

Package Marking and Ordering Information

| Device Marking | Device | Package | Packing | Reel Size | Tape Width | Quantity |
|-----------------------------|-----------------------------|----------|-------------|-----------|------------|----------|
| Refer to Product table list | Refer to Product table list | SOD-523F | Tape & Reel | 7" | 12mm | 3,000 |


Electrical Characteristics T_A=25°C unless otherwise noted

| Device Type | Device Marking | V _Z (V) @ I _{ZT} | | | Z _{ZT} (Ω) @ I _{ZT} | I _{ZT} (mA) | Z _{ZK} (Ω) @ I _{ZK} | I _{ZK} (mA) | I _R (μA) @ V _R | V _R (V) |
|-------------|----------------|--------------------------------------|------|------|--|-------------------------|--|-------------------------|---|--------------------|
| | | Min. | Typ. | Max. | Max. | - | Max. | - | Max | - |
| MM5Z2V4 | 50 | 2.2 | 2.4 | 2.6 | 100 | 5 | 1000 | 1 | 50 | 1 |
| MM5Z2V7 | 51 | 2.5 | 2.7 | 2.9 | 100 | 5 | 1000 | 1 | 20 | 1 |
| MM5Z3V0 | 52 | 2.8 | 3.0 | 3.2 | 100 | 5 | 1000 | 1 | 10 | 1 |
| MM5Z3V3 | 53 | 3.1 | 3.3 | 3.5 | 95 | 5 | 1000 | 1 | 5 | 1 |
| MM5Z3V6 | 54 | 3.4 | 3.6 | 3.8 | 90 | 5 | 1000 | 1 | 5 | 1 |
| MM5Z3V9 | 55 | 3.7 | 3.9 | 4.1 | 90 | 5 | 1000 | 1 | 3 | 1 |
| MM5Z4V3 | 56 | 4.0 | 4.3 | 4.6 | 90 | 5 | 1000 | 1 | 3 | 1 |
| MM5Z4V7 | 57 | 4.4 | 4.7 | 5.0 | 80 | 5 | 800 | 1 | 3 | 2 |
| MM5Z5V1 | 58 | 4.8 | 5.1 | 5.4 | 60 | 5 | 500 | 1 | 2 | 2 |
| MM5Z5V6 | 59 | 5.2 | 5.6 | 6.0 | 40 | 5 | 200 | 1 | 1 | 2 |
| MM5Z6V2 | 5A | 5.8 | 6.2 | 6.6 | 10 | 5 | 100 | 1 | 3 | 4 |
| MM5Z6V8 | 5B | 6.4 | 6.8 | 7.2 | 15 | 5 | 160 | 1 | 2 | 4 |
| MM5Z7V5 | 5C | 7.0 | 7.5 | 7.9 | 15 | 5 | 160 | 1 | 1 | 5 |
| MM5Z8V2 | 5D | 7.7 | 8.2 | 8.7 | 15 | 5 | 160 | 1 | 0.7 | 5 |
| MM5Z9V1 | 5E | 8.5 | 9.1 | 9.6 | 15 | 5 | 160 | 1 | 0.2 | 7 |
| MM5Z10V | 5F | 9.4 | 10 | 10.6 | 20 | 5 | 160 | 1 | 0.1 | 8 |
| MM5Z11V | 5G | 10.4 | 11 | 11.6 | 20 | 5 | 160 | 1 | 0.1 | 8 |
| MM5Z12V | 5H | 11.4 | 12 | 12.7 | 25 | 5 | 80 | 1 | 0.1 | 8 |
| MM5Z13V | 5J | 12.4 | 13 | 14.1 | 30 | 5 | 80 | 1 | 0.1 | 8 |
| MM5Z15V | 5K | 14.3 | 15 | 15.8 | 30 | 5 | 80 | 1 | 0.05 | 10.5 |
| MM5Z16V | 5L | 15.3 | 16 | 17.1 | 40 | 5 | 80 | 1 | 0.05 | 11.2 |
| MM5Z18V | 5M | 16.8 | 18 | 19.1 | 45 | 5 | 80 | 1 | 0.05 | 12.6 |
| MM5Z20V | 5N | 18.8 | 20 | 21.2 | 55 | 5 | 100 | 1 | 0.05 | 14.0 |
| MM5Z22V | 5P | 20.8 | 22 | 23.3 | 55 | 5 | 100 | 1 | 0.05 | 15.4 |
| MM5Z24V | 5R | 22.8 | 24 | 25.6 | 70 | 5 | 120 | 1 | 0.05 | 16.8 |
| MM5Z27V | 5S | 25.1 | 27 | 28.9 | 80 | 2 | 300 | 0.5 | 0.05 | 18.9 |
| MM5Z30V | 5T | 28 | 30 | 32 | 80 | 2 | 300 | 0.5 | 0.05 | 21.0 |
| MM5Z33V | 5U | 31 | 33 | 35 | 80 | 2 | 300 | 0.5 | 0.05 | 23.2 |
| MM5Z36V | 5V | 34 | 36 | 38 | 90 | 2 | 500 | 0.5 | 0.05 | 25.2 |
| MM5Z39V | 5X | 37 | 39 | 41 | 130 | 2 | 500 | 0.5 | 0.05 | 27.3 |
| MM5Z43V | 5Y | 40 | 43 | 46 | 150 | 2 | 500 | 0.5 | 0.05 | 30.1 |
| MM5Z47V | 5Z | 44 | 47 | 50 | 170 | 2 | 500 | 0.5 | 0.05 | 32.9 |
| MM5Z51V | 5- | 48 | 51 | 54 | 180 | 2 | 500 | 0.5 | 0.05 | 35.7 |
| MM5Z56V | 5= | 52 | 56 | 60 | 200 | 2 | 500 | 0.5 | 0.05 | 39.2 |
| MM5Z62V | 5≡ | 58 | 62 | 66 | 215 | 2 | 500 | 0.5 | 0.05 | 43.4 |
| MM5Z68V | 5> | 64 | 68 | 72 | 240 | 2 | 500 | 0.5 | 0.05 | 47.6 |
| MM5Z75V | 5< | 70 | 75 | 79 | 255 | 2 | 500 | 0.5 | 0.05 | 52.5 |

NOTES:

- 1) The Zener Voltage (V_Z) is tested under pulse condition of 10mS.
- 2) The Zener impedance is derived from the 60-cycle AC voltage, which results when an AC current having an RMS value equal to 10% of the DC Zener current (I_{ZT} or I_{ZK}) is superimposed to I_{ZT} or I_{ZK}.

SOD-523F Package Outline






NOTES; UNLESS OTHERWISE SPECIFIED

- A) PACKAGE REFERENCE; THIS PACKAGE OUTLINE CONFORMS TO JEITA SC-79.
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DRAWING CONFORMS TO ASME Y14.5M - 1994
- D) DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- E) LANDPATTERN RECOMMENDATION IS BASED ON IPC7351A STANDARD SOD1609X65M.
- F) DRAWING NUMBER AND REVISION;MKT-SOD523F1rev1



TRADEMARKS

The following are registered and unregistered trademarks and service marks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

| | | | |
|---|---|--|---|
| ACEx [®] | Green FPS [™] | Power247 [®] | SuperSOT [™] -8 |
| Build it Now [™] | Green FPS [™] e-Series [™] | POWEREDGE [®] | SyncFET [™] |
| CorePLUS [™] | GTO [™] | Power-SPM [™] | The Power Franchise [®] |
| CROSSVOLT [™] | <i>i-Lo</i> [™] | PowerTrench [®] |  |
| CTL [™] | IntelliMAX [™] | Programmable Active Droop [™] | TinyBoost [™] |
| Current Transfer Logic [™] | ISOPLANAR [™] | QFET [®] | TinyBuck [™] |
| EcoSPARK [®] | MegaBuck [™] | QS [™] | TinyLogic [®] |
|  | MICROCOUPLER [™] | QT Optoelectronics [™] | TINYOPTO [™] |
| Fairchild [®] | MicroFET [™] | Quiet Series [™] | TinyPower [™] |
| Fairchild Semiconductor [®] | MicroPak [™] | RapidConfigure [™] | TinyPWM [™] |
| FACT Quiet Series [™] | Motion-SPM [™] | SMART START [™] | TinyWire [™] |
| FACT [®] | OPTOLOGIC [®] | SPM [®] | μSerDes [™] |
| FAST [®] | OPTOPLANAR [®] | STEALTH [™] | UHC [®] |
| FastvCore [™] |  | SuperFET [™] | UniFET [™] |
| FPS [™] | PDP-SPM [™] | SuperSOT [™] -3 | VCX [™] |
| FRFET [®] | Power220 [®] | SuperSOT [™] -6 | |
| Global Power Resource SM | | | |

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

| Datasheet Identification | Product Status | Definition |
|--------------------------|------------------------|--|
| Advance Information | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| Obsolete | Not In Production | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only. |

Rev. I30