



T.			U_f	I_f	U_{tr}	U_p	I_o	I_p	$U_{g\ max}$	$I_{g\ max}$	$t_{min\div\ max}$
			V	A	V	V	mA	mA	V	mA	°C
ASG 5023	AEG	6	2,5	7	1250	1250	1500	6000	-125	10 ÷ 50	-10 ÷ +45
BT 19	BTH	1	2,5	5	1000	1000	500	2000	-6	100	+15 ÷ +40
BT 75	BTH	1	2,5	11	1000	1250	250	15000		100	
BT 89	BTH	1	2,5	5	1000	1500	500	2000		100	-40 ÷ +80
C 1 K	Elc	2	2,5	6,3	1000	1250	1000	8000	-4,5 ÷ -100		-55 ÷ +75
C 3 H	Elc	7	2,5	9	1000	1250	2800	20000	-13 ÷ -100		-55 ÷ +75
S 1/3 dM	AEG	3	2,5	8	1000		1000	3000			
3 C 23	amer	10	2,5	7	1250	1250	1500	6000	-4,5 ÷ -500	10 ÷ 50	-40 ÷ +80
3 V/340 B	STCE	1	2,5	5	1000	1500	500	2000	-4	25 ÷ 100	+15 ÷ +40
287 A	amer	9	2,5	7	1250	1250	1500	6000	-500		+30 ÷ +80
304	Cet	8	2,5	21	1000	1000	12500	125 A	+7,5 ÷ -100		+40 ÷ +80
311	Cet	10	2,5	7	1000	1000	1500	6000	-3,75 ÷ -500	10 ÷ 50	-40 ÷ +80
323 B	amer	9	2,5	7	1250	1250	1500	6000	-500		-40 ÷ +80
394 A	amer	4	2,5	3,2	1250	1250	640	2500	-4 ÷ -100		-40 ÷ +80
627	amer	5	2,5	6	1250	2500	640	2500	-500	60 ÷ 250	+25 ÷ +70
740	amer	8	2,5	16	1000	1250	4000	30000	-500		-40 ÷ +80
5684	int	7	2,5	9	1000	1250	2500	30000	-6 ÷ -100		-55 ÷ +70
5685	int	5	2,5	21	1000	1250	6400	77000	-4,6 ÷ -100		-55 ÷ +70
5796	amer	7	2,5	8,5	1500	1500	1600	20000	-250	100	
6011	GE	7	2,5	9	1250	1250	2500	10000	-6		-40 ÷ +80

Equivalents

C 3 J/A	Elc = 5684	ELC 1 K	Elc = C 1 K	TQ 1/2	BB = 3 C 23
C 6 J/A	Elc = 5685	ELC 3 H	Elc = C 3 H	WL 5684	Wst = 5684
C 6 M	Elc = 5685	ELC 3 J/A	Elc = 5684	WL 5685	Wst = 5685
C 6 P	Elc = 5685	ELC 6 J/A	Elc = 5685	WL 5296	Wst = 5796
CE 304	Cet = 304	ELC 6 M	Elc = 5685	393 A	amer = 323 B
CE 311	Cet = 311	ELC 6 P	Elc = 5685	610	amer = 6011
CE 393 A	Cet = 323 B	FG 97	GE = RT 19	740 P	amer = 740
CT 1-500	Mul = BT 19	KU 627	Wst = 627	1287 A	amer = 287 A
				5785	amer = 5685

