



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	8.28	8.53	0.326	0.336
B	10.05	10.31	0.396	0.406
C	4.31	4.57	0.170	0.180
D	0.66	0.91	0.026	0.036
E	1.14	1.40	0.045	0.055
F	1.47	1.98	0.058	0.078
G	1.27 BSC		0.050 BSC	
H	2.54	2.79	0.100	0.110
J	0.46	0.64	0.018	0.025
K	5.18	5.44	0.204	0.214
M	1.40	1.68	0.055	0.066
N	0.00	0.10	0.000	0.004
U	6.50 REF		0.256 REF	
V	7.75 REF		0.305 REF	

NOTES:

- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
- CONTROLLING DIMENSION: INCH.
- TAB CONTOUR OPTIONAL WITHIN DIMENSIONS B AND M.
- DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH OR GATE PROTRUSIONS. MOLD FLASH AND GATE PROTRUSIONS NOT TO EXCEED 0.025(0.635) MAX.

CASE NO.	936H-01
STATUS	ON SEMICONDUCTOR STANDARD
NEW STD	
USED ON	



ISSUE	REVISION	COORD/ DATE
0	INITIAL RELEASE REQ BY T. GRINTER	FB 09 AUG 00