


2SC4059

(T15W45FX)

15A NPN

OUTLINE DIMENSIONS



RATINGS

● Absolute Maximum Ratings


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T_{stg}		-55~150	°C
Junction Temperature	T_j		150	°C
Collector to Base Voltage	V_{CBO}		600	V
Collector to Emitter Voltage	V_{CEO}		450	V
	V_{CEX}	$V_{EB} = 5V$	600	
Emitter to Base Voltage	V_{EBO}		7	V
Collector Current DC	I_C		15	A
Collector Current Peak	I_{CP}		30	
Base Current DC	I_B		6	A
Base Current Peak	I_{BP}		12	
Total Transistor Dissipation	P_T	$T_c = 25^\circ C$	130	W
Mounting Torque	TOR		0.8	N·m

● Electrical Characteristics ($T_c=25^\circ C$)


Item	Symbol	Conditions	Ratings	Unit
Collector to Emitter Sustaining Voltage	$V_{CEO}(sus)$	$I_C = 0.2A$	Min 450	V
Collector Cutoff Current	I_{CBO}	At rated Voltage	Max 0.1	mA
	I_{CEO}		Max 0.1	
Emitter Cutoff Current	I_{EBO}	At rated Voltage	Max 0.1	mA
DC Current Gain	h_{FE}	$V_{CE} = 5V, I_C = 7.5A$	Min 10	
	h_{FEL}	$V_{CE} = 5V, I_C = 1mA$	Min 5	
Collector to Emitter Saturation Voltage	$V_{CE}(sat)$	$I_C = 7.5A$	Max 1.0	V
Base to Emitter Saturation Voltage	$V_{BE}(sat)$	$I_B = 1.5A$	Max 1.5	V
Thermal Resistance	θ_{jc}	Junction to case	Max 0.96	°C/W
Transition Frequency	f_T	$V_{CE} = 10V, I_C = 1.5A$	STD 20	MHz
Turn on Time	t_{on}	$I_C = 7.5A$	Max 0.5	μs
Storage Time	t_s	$I_{B1} = 1.5A, I_{B2} = 3A$	Max 2.0	
Fall Time	t_f	$R_L = 20\Omega, V_{BB2} = 4V$	Max 0.2	

2SC4059

$h_{FE} - I_C$




2SC4059 Saturation Voltage




2SC4059

Switching Time - I_C




2SC4059 Switching Time - V_{CC}




2SC4059


Switching Time - Tc




2SC4059 L-Load Switching Time - I_C



2SC4059 L-Load Switching Time - I_C (At High Temperature)




2SC4059 Transient Thermal Impedance



2SC4059

Forward Bias SOA



2SC4059 Collector Current Derating



2SC4059

Reverse Bias SOA

