

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:


The **ASI 3000** is Designed for General Purpose Class C Power Amplifier Applications up to 3500 MHz.

FEATURES:

- $P_G = 7$ dB min. at 0.5 W / 3,000 MHz
- Hermetic Microstrip Package
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	0.1 A
V_{CC}	30 V
P_{DISS}	2.5 W @ $T_C = 25^\circ C$
T_J	$-65^\circ C$ to $+200^\circ C$
T_{STG}	$-65^\circ C$ to $+200^\circ C$
θ_{JC}	$45^\circ C/W$

PACKAGE STYLE .250 2L FLG


DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.028 / 0.71	.032 / 0.81
B	.740 / 18.80	
C	.245 / 6.22	.255 / 6.48
D	.128 / 3.25	.132 / 3.35
E		.125 / 3.18
F	.110 / 2.79	.117 / 2.97
G		.117 / 2.97
H	.560 / 14.22	.570 / 14.48
I	.790 / 20.07	.810 / 20.57
J	.225 / 5.72	.235 / 5.97
K	.165 / 4.19	.185 / 4.70
L	.003 / 0.08	.007 / 0.18
M	.058 / 1.47	.068 / 1.73
N	.119 / 3.02	.135 / 3.43
P	.149 / 3.78	.187 / 4.75

ORDER CODE: ASI10537
CHARACTERISTICS $T_C = 25^\circ C$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CBO}	$I_C = 1$ mA	50			V
BV_{CER}	$I_C = 5$ mA $R_{BE} = 10 \Omega$	50			V
BV_{EBO}	$I_E = 1$ mA	3.5			V
I_{CBO}	$V_{CE} = 28$ V			250	mA
h_{FE}	$V_{CE} = 5.0$ V $I_C = 50$ mA	15		120	---
C_{OB}	$V_{CB} = 28$ V $f = 1.0$ MHz			2.5	pF
P_G	$V_{CC} = 28$ V $P_{OUT} = 0.5$ W $f = 3.0$ GHz	7.0			dB
η_C		30			%