

# NPN SILICON RF POWER TRANSISTOR

**DESCRIPTION:**

The **ASI AVF250** is Designed for Class C, IFF Applications up to 1090 MHz.

**FEATURES:**

- Internal Input/Output Matching Networks
- $P_G = 8.5$  dB at 250 W/1090 MHz
- **Omnigold™** Metalization System

**MAXIMUM RATINGS**

$I_C$	18.8 A
$V_{CC}$	55 V
$P_{DISS}$	625 W @ $T_C = 25$ °C
$T_J$	-65 °C to +2500 °C
$T_{STG}$	-65 °C to +200 °C
$\theta_{JC}$	0.6 °C/W

**PACKAGE STYLE .400 2NL FLG**

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.020 / 0.51	.030 / 0.76
B	.100 / 2.54	
C	.376 / 9.55	.396 / 10.06
D	.110 / 2.79	.130 / 3.30
E	.395 / 10.03	.407 / 10.34
F	.193 / 4.90	
G	.450 / 11.43	
H	.125 / 3.18	
I	.640 / 16.26	.660 / 16.76
J	.890 / 22.61	.910 / 23.11
K	.395 / 10.03	.415 / 10.54
L	.004 / 0.10	.007 / 0.18
M	.052 / 1.32	.072 / 1.83
N	.118 / 3.00	.131 / 3.33
P		.230 / 5.84

**ORDER CODE: ASI10571**

**CHARACTERISTICS**  $T_C = 25$  °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
$BV_{CBO}$	$I_C = 10$ Ma	65			V
$BV_{CER}$	$I_C = 25$ mA $R_{BE} = 10$ Ω	65			V
$BV_{EBO}$	$I_E = 1.0$ mA	3.5			V
$I_{CES}$	$V_{CE} = 50$ V			25	mA
$h_{FE}$	$V_{CE} = 5.0$ V $I_C = 1.0$ A	15		120	---
$P_G$	$V_{CC} = 50$ V $P_{OUT} = 250$ W $f = 1030 - 1090$ MHz	8.5			dB
$\eta_c$		35			%