



**MDA100A series
(3N246 thru
3N252)**

MINIATURE INTEGRAL DIODE ASSEMBLIES

... with silicon rectifier chips interconnected and encapsulated into voidless rectifier bridge circuits.

- High Resistance to Shock and Vibration
- High Dielectric Strength
- Built-In Printed Circuit Board Stand-Offs
- UL Recognized
- ROJA = 60°C/W


**SINGLE-PHASE
FULL-WAVE BRIDGE**
**1.0 AMPERE
50-1000 VOLTS**



MAXIMUM RATINGS	Rating (Per Diode)	Symbol									Unit
			3N246 MDA100A	3N247 MDA101A	3N248 MDA102A	3N249 MDA104A	3N250 MDA106A	3N251 MDA108A	3N252 MDA110A		
Peak Repetitive Reverse Voltage	VRRM		50	100	200	400	600	800	1000	Volts	
Working Peak Reverse Voltage	VRWM										
DC Blocking Voltage	VR										
DC Output Voltage	Vdc	Resistive Load	32	64	127	255	382	510	640	Volts	
		Capacitive Load	50	100	200	400	600	800	1000	Volts	
Sine Wave RMS Input Voltage	VR(RMS)		35	70	140	280	420	560	700	Volts	
Average Rectified Forward Current (single phase bridge operation, resistive load, 60 Hz, TA = 75°C)	IO		1.0							Amp	
Non Repetitive Peak Surge Current (Preceded and followed by rated current and voltage, TA = 75°C)	IFSM		30 (for 1 cycle)							Amp	
Operating and Storage Junction Temperature Range	TJ, Tstg		-55 to +150							°C	


ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Typ	Max	Unit
Instantaneous Forward Voltage (Per Diode) (IF = 1.57 Amp, TJ = 25°C)	V _F	1.15	1.3	Volts
Reverse Current (Per Diode) (Rated VR, TA = 25°C)	I _R	-	10	µA

MECHANICAL CHARACTERISTICS

CASE: Transfer Moulded Plastic
POLARITY: Terminal-designation on case
Pin 1 (+) for DC output
Pin 4 (-) for DC output
Pins 2 and 3 (AC) for AC input

MOUNTING POSITION: Any
WEIGHT: 1.8 grams (approx)
TERMINALS: Readily solderable
connections, corrosion resistant.



STYLE 1:
TERM 1 POS
2 AC
3 AC
4 NEG

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	14.99	15.49	0.590	0.610
B	4.57	5.08	0.180	0.200
C	-	20.57	-	0.810
D	0.76	1.02	0.030	0.040
F	1.02	1.27	0.040	0.050
G	3.68	3.94	0.145	0.155
J	0.56	0.71	0.022	0.028
K	-	9.02	-	0.355
L	1.78	2.03	0.070	0.080
N	2.54	2.79	0.100	0.110
R	9.40	10.03	0.370	0.395

NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.