

DT 75/30

RX 75/10

RG 59 B/U

DT 59/8

Applicazioni Applications

DT 75/30

Trasmissione dati
Data transmission

Video

CCTV

RX 75/10

Trasmissione dati
Data transmission

Video

CCTV

RG 59 B/U

Trasmissione dati
Data transmission

Video

CCTV

DT 59/8

Trasmissione dati
Data transmission

Video

CCTV

Conduttore interno Inner conductor	CW 1 x 0.40 ø = 0.40 mm	Cu 7 x 0.20 ø = 0.60 mm	CW 1 x 0.58 ø = 0.58 mm	CW 1 x 0.58 ø = 0.58 mm
Materiale isolamento Insulation material	PE ø = 2.50 mm	PE ø = 3.70 mm	PE ø = 3.70 mm	PE ø = 3.70 mm
Schermo Shield	Cu	Cu	Cu	Cu
Guaina Jacket	PVC ø = 4.00 mm	PVC ø = 6.10 mm	PVC ø = 6.15 mm	PVC ø = 6.15 mm
Peso Weight	25 kg/km	50 kg/km	46 kg/km	45 kg/km
Impedenza caratteristica Characteristic impedance	75 ± 3 Ω	75 ± 3 Ω	75 ± 3 Ω	75 ± 3 Ω
Capacità Capacitance	67 nF/km	67 nF/km	67 nF/km	67 nF/km
Velocità di propagazione Propagation velocity	66%	66%	66%	66%
Attenuazione dB/100 m Attenuation dB/100 m				
5 MHz	3.70	2.50	2.20	2.20
10 MHz	5.20	3.60	3.20	3.20
50 MHz	11.50	8.10	7.90	7.90
100 MHz	16.50	12.20	11.20	11.20
200 MHz	25.00	17.10	16.10	16.10
400 MHz	36.00	24.30	23.30	23.30
1000 MHz	58.40	41.50	39.40	39.40