

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet **Halogen Free** **Firestop®** **RoHS₃**

tasker® RG 59 PUR 75 Ω
Coaxial Mil. C 17 F Standard Cable – Outdoor Use



A	B	C	D
---	---	---	---

CATEGORY
APPLICATIONS

Coaxial cable 75 Ω (See Video Catalogue)
 Premade video Cables and Broadcast.

- A:** Black Polyurethane **PUR** Sheath. Outer Diam. Ø 6,40 (±0,20) mm
 Flame Retardant, Halogen Free and UV, Water, Chemical and Oil Resistant.
- B:** Shielding O.F.C. red copper Braid covering 98%.
- C:** Core Insulation with transparent compact PE. Diam. Ø 3,70 (±0,20) mm.
- D:** Stiff Wire in CW Formation 1x0,58 mm.
 Nom. Cross section 1x0,26 mm²

MARKING
AVAILABLE ALSO

tasker® RG59 PUR 75 Ohm Mil.- C17/F Outdoor use video cable – Made in Italy
 RG59 BU, RG59 Flex, RG59 LSZH, RG59 Special, RG59 Extra, RG59 AR

CUSTOM
PRODUCTION

This product may be custom produced also in **PE**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	158 Ω/Km
Capacity Core/Shield	67 pF/mt
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	2.000 V
Operative Temperature	-40/+80°C

Attenuation dB/100 m.

50 MHz	7,4
100 MHz	10,7
200 MHz	15,7
400 MHz	22,7
800 MHz	33,6
1000 MHz	38,0

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
	X	Outdoor	Esterno			Mobile	Mobile			
	X	Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			