

Solid Tantalum Surface Mount Capacitors TANTAMOUNT[®], Molded Case, DSCC Approved, Built-In Fuse


FEATURES

- Terminations: Tin/lead solder plated
- Molded package available in 3 case codes
- Meets MIL-PRF-55365 and EIA535BAAC mechanical and performance requirements
- Compliant terminations
- Electrically activated internal fuse

Reliability Grade

Weibull B (0.1 %), C (0.01 %) and D (0.001 %) per MIL-PRF-55365

Non-Weibull Z: Voltage aging a minimum of 10 h at 1.32 times rated voltage

100 % Surge Current Tested

- Temperature: 25 °C
- Applied voltage: Rated voltage
- Test cycles: 4
- Charge and discharge cycles: 4 s maximum
- Total DC resistance: 1.2 Ω maximum

PERFORMANCE/ELECTRICAL CHARACTERISTICS

Operating Temperature: - 55 °C to + 125 °C
(above 85 °C, voltage derating is required)

Capacitance Range: 0.47 μF to 470 μF

Capacitance Tolerance: ± 20 %

Voltage Rating: 4 V_{DC} to 50 V_{DC}

ORDERING INFORMATION			
<u>04053-</u> DRAWING NUMBER	<u>001</u> DASH NUMBER	<u>Z</u> RELIABILITY GRADE (% per 1000 h)	<u>T</u> PACKAGING
		<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: auto;"> B: 0.1 % C: 0.01 % D: 0.001 % Z: Non-Weibull </div>	<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: auto;"> T = 7" (178 mm) reel </div>


DIMENSIONS in inches [millimeters]							
CASE CODE	EIA SIZE	L	W	H	P	T _w	T _H MIN.
C	6032-28	0.236 ± 0.012 [6.0 ± 0.30]	0.126 ± 0.012 [3.2 ± 0.30]	0.098 ± 0.012 [2.5 ± 0.30]	0.051 ± 0.012 [1.3 ± 0.30]	0.087 ± 0.004 [2.2 ± 0.10]	0.039 [1.0]
D	7343-31	0.287 ± 0.012 [7.3 ± 0.30]	0.170 ± 0.012 [4.3 ± 0.30]	0.110 ± 0.012 [2.8 ± 0.30]	0.051 ± 0.012 [1.3 ± 0.30]	0.095 ± 0.004 [2.4 ± 0.10]	0.039 [1.0]
E	7343-43	0.287 ± 0.012 [7.3 ± 0.30]	0.170 ± 0.012 [4.3 ± 0.30]	0.158 ± 0.012 [4.0 ± 0.30]	0.051 ± 0.012 [1.3 ± 0.30]	0.095 ± 0.004 [2.4 ± 0.10]	0.039 [1.0]

RATINGS AND CASE CODES								
μF	4 V	6 V	10 V	16 V	20 V	25 V	35 V	50 V
0.47								C
0.68								C
1.0								C
1.5							C	C
2.2						C	C	D
3.3						C	C	D
4.7					C	C	D	
6.8				C	C	C	D	
10			C	C	C	C/D	E	
15		C	C	C	D	D	E	
22		C	C	C/D	D	D/E	E	
33		C	C/D	D	E			
47		C	C/D	D/E	E			
68	C	C/D	D/E					
100	C	D/E	D	E				
150	D	D	D/E					
220	D	D/E	E					
330	D/E	E						
470	E							

MARKING

"C, D, E" case sizes

Marking:
 The capacitor shall be marked with an anode (+) polarity band, capacitance (in microfarads) and the rated DC working voltage 85 °C. The capacitance voltage will be separated by the letter "F" indicating a fused capacitor. The Vishay Sprague® trademark is included. A manufacturing date code is marked on all capacitors.





STANDARD RATINGS						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DC LEAKAGE AT + 25 °C (μ A)	MAX. DF AT + 25 °C 120 Hz (%)	MAX. ESR AT + 25 °C 100 kHz (Ω)	
4 V_{DC} AT + 85 °C; 2.7 V_{DC} AT + 125 °C						
68	C	04053-001(1)(2)	2.7	6	1.600	
100	C	04053-002(1)(2)	4.0	8	1.200	
150	D	04053-003(1)(2)	6.0	8	0.800	
220	D	04053-004(1)(2)	8.8	8	0.700	
330	D	04053-005(1)(2)	13.2	8	0.700	
330	E	04053-006(1)(2)	13.2	8	0.700	
470	E	04053-007(1)(2)	18.8	8	0.500	
6 V_{DC} AT + 85 °C; 4 V_{DC} AT + 125 °C						
15	C	04053-011(1)(2)	0.9	6	2.000	
22	C	04053-013(1)(2)	1.4	6	2.000	
33	C	04053-014(1)(2)	2.0	6	2.000	
47	C	04053-016(1)(2)	2.9	6	1.600	
47	D	04053-015(1)(2)	2.9	6	1.000	
68	C	04053-018(1)(2)	4.1	6	1.200	
68	D	04053-017(1)(2)	4.1	6	1.000	
100	D	04053-020(1)(2)	6.0	8	0.800	
100	E	04053-019(1)(2)	6.0	8	0.900	
150	D	04053-021(1)(2)	9.0	8	0.700	
220	D	04053-022(1)(2)	13.2	8	0.700	
220	E	04053-023(1)(2)	13.2	8	0.700	
330	E	04053-024(1)(2)	19.8	8	0.500	
10 V_{DC} AT + 85 °C; 7 V_{DC} AT + 125 °C						
10	C	04053-028(1)(2)	1.0	6	2.000	
15	C	04053-030(1)(2)	1.5	6	2.000	
22	C	04053-031(1)(2)	2.2	6	2.000	
33	C	04053-033(1)(2)	3.3	6	1.600	
33	D	04053-032(1)(2)	3.3	6	1.000	
47	C	04053-035(1)(2)	4.7	6	1.200	
47	D	04053-034(1)(2)	4.7	6	1.000	
68	D	04053-037(1)(2)	6.8	6	0.800	
68	E	04053-036(1)(2)	6.8	6	0.900	
100	D	04053-038(1)(2)	10.0	8	0.700	
150	D	04053-040(1)(2)	15.0	8	0.700	
150	E	04053-039(1)(2)	15.0	8	0.700	
220	E	04053-041(1)(2)	22.0	8	0.500	
16 V_{DC} AT + 85 °C; 10 V_{DC} AT + 125 °C						
6.8	C	04053-045(1)(2)	1.1	6	2.000	
10	C	04053-047(1)(2)	1.6	6	2.000	
15	C	04053-048(1)(2)	2.4	6	2.000	
22	C	04053-050(1)(2)	3.5	6	1.600	
22	D	04053-049(1)(2)	3.5	6	1.000	
33	D	04053-051(1)(2)	5.3	6	1.000	
47	D	04053-053(1)(2)	7.5	6	0.800	
47	E	04053-052(1)(2)	7.5	6	0.900	
100	E	04053-054(1)(2)	16.0	8	0.700	

Note

- Part number definitions:
 - (1) Reliability grade: B, C, D, Z
 - (2) Packaging codes: T



STANDARD RATINGS						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DC LEAKAGE AT + 25 °C (μ A)	MAX. DF AT + 25 °C 120 Hz (%)	MAX. ESR AT + 25 °C 100 kHz (Ω)	
20 V_{DC} AT + 85 °C; 13 V_{DC} AT + 125 °C						
4.7	C	04053-058(1)(2)	1.0	6	2.000	
6.8	C	04053-059(1)(2)	1.4	6	2.000	
10	C	04053-060(1)(2)	2.0	6	2.000	
15	D	04053-061(1)(2)	3.0	6	1.000	
22	D	04053-062(1)(2)	4.4	6	1.000	
33	E	04053-063(1)(2)	6.6	6	0.900	
47	E	04053-064(1)(2)	9.4	6	0.300	
25 V_{DC} AT + 85 °C; 17 V_{DC} AT + 125 °C						
2.2	C	04053-068(1)(2)	0.6	6	3.500	
3.3	C	04053-069(1)(2)	0.9	6	2.500	
4.7	C	04053-070(1)(2)	1.2	6	2.500	
6.8	C	04053-071(1)(2)	1.7	6	2.000	
10	C	04053-072(1)(2)	2.5	6	0.600	
10	D	04053-073(1)(2)	2.5	6	1.200	
15	D	04053-074(1)(2)	3.8	6	1.000	
22	D	04053-076(1)(2)	5.5	6	0.800	
22	E	04053-075(1)(2)	5.5	6	0.900	
35 V_{DC} AT + 85 °C; 23 V_{DC} AT + 125 °C						
1.5	C	04053-080(1)(2)	0.5	6	4.500	
2.2	C	04053-081(1)(2)	0.8	6	3.500	
3.3	C	04053-082(1)(2)	1.2	6	2.500	
4.7	D	04053-083(1)(2)	1.7	6	1.500	
6.8	D	04053-084(1)(2)	2.4	6	1.300	
10	E	04053-085(1)(2)	3.5	6	1.000	
15	E	04053-086(1)(2)	5.3	6	0.900	
22	E	04053-087(1)(2)	7.7	6	0.300	
50 V_{DC} AT + 85 °C; 33 V_{DC} AT + 125 °C						
0.47	C	04053-091(1)(2)	0.5	4	8.000	
0.68	C	04053-092(1)(2)	0.5	4	7.000	
1.0	C	04053-093(1)(2)	0.5	4	5.500	
1.5	C	04053-094(1)(2)	0.8	6	5.000	
2.2	D	04053-095(1)(2)	1.1	6	2.500	
3.3	D	04053-096(1)(2)	1.7	6	2.000	

Note

- Part number definitions:
 - Reliability grade: B, C, D, Z
 - Packaging codes: T



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.