




Carvic International Ltd.

## B40C1500 THRU B500C1500

<p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>● Plastic material used carried Underwriters laboratory recognition.</li> <li>● High case Dielectric strength.</li> <li>● Typical <math>I_r</math> less than 1 <math>\mu</math> A.</li> <li>● Exceeds environmental standards of MIL-STD-19500.</li> <li>● Ideal for printed circuit board.</li> <li>● High temperature soldering guaranteed: 265°C /10 seconds / .375." , (9.5mm) lead length at 5 lbs., (2.3kg) tension.</li> </ul> <p><b>MECHANICAL DATA</b></p> <p>Case: Reliable low cost construction utilizing molded plastic technique.</p> <p>Terminals: Leads, solderable per MIL-STD-202, Method 208.</p> <p>Mounting position: Any.</p> <p>Weight: 0.04 ounces, 1.1 grams.</p>	<p><b>VOLTAGE RANGE</b> 90 to 1200 Volts</p> <p><b>CURRENT</b> 1.5 Amperes</p> <p><b>RB-10</b></p>  <p>Dimensions in inches and (millimeters)</p>																																																																																																								
<p><b>MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS</b></p> <p>Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load 60 Hz. For capacitive load, derate current by 20%.</p>																																																																																																									
	<table border="1"> <thead> <tr> <th></th> <th>B40C1500</th> <th>B80C1500</th> <th>B125C1500</th> <th>B250C1500</th> <th>B380C1500</th> <th>B500C1500</th> <th>UNITS</th> </tr> </thead> <tbody> <tr> <td>Maximum Recurrent Peak Reverse Voltage</td> <td>90</td> <td>180</td> <td>350</td> <td>600</td> <td>900</td> <td>1200</td> <td>V<sub>RRM</sub></td> </tr> <tr> <td>Maximum RMS Bridge Input Voltage</td> <td>70</td> <td>140</td> <td>280</td> <td>420</td> <td>560</td> <td>700</td> <td>V<sub>RMS</sub></td> </tr> <tr> <td>Maximum DC Blocking Voltage</td> <td>90</td> <td>180</td> <td>350</td> <td>600</td> <td>900</td> <td>1000</td> <td>V<sub>DC</sub></td> </tr> <tr> <td>Maximum Average Forward Rectified Current 373" (9.5mm) Lead Lengths at T<sub>A</sub>=25°C</td> <td colspan="6">1.5</td> <td>A(AV)</td> </tr> <tr> <td>Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC Method)</td> <td colspan="6">50</td> <td>A<sup>2</sup>S</td> </tr> <tr> <td>I<sup>2</sup> t Rating for Fusing (t&lt;.00835ms)</td> <td colspan="6">5.0</td> <td></td> </tr> <tr> <td>Maximum Forward Voltage Drop per Element at 1.0A</td> <td colspan="6">1.0</td> <td>V</td> </tr> <tr> <td>Maximum DC Reverse Current, at rated DC Blocking Voltage</td> <td colspan="6">10.0</td> <td><math>\mu</math> A</td> </tr> <tr> <td></td> <td colspan="6">1.0</td> <td>mA</td> </tr> <tr> <td>Typical Junction Capacitance per Bridge Element</td> <td colspan="6">24.0</td> <td>PF</td> </tr> <tr> <td>Operating Temperature Range ,T<sub>A</sub></td> <td colspan="6">- 65 To + 125</td> <td>°C</td> </tr> <tr> <td>Storage Temperature Range T<sub>STG</sub></td> <td colspan="6">- 65 To + 150</td> <td>°C</td> </tr> </tbody> </table>		B40C1500	B80C1500	B125C1500	B250C1500	B380C1500	B500C1500	UNITS	Maximum Recurrent Peak Reverse Voltage	90	180	350	600	900	1200	V <sub>RRM</sub>	Maximum RMS Bridge Input Voltage	70	140	280	420	560	700	V <sub>RMS</sub>	Maximum DC Blocking Voltage	90	180	350	600	900	1000	V <sub>DC</sub>	Maximum Average Forward Rectified Current 373" (9.5mm) Lead Lengths at T <sub>A</sub> =25°C	1.5						A(AV)	Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC Method)	50						A <sup>2</sup> S	I <sup>2</sup> t Rating for Fusing (t<.00835ms)	5.0							Maximum Forward Voltage Drop per Element at 1.0A	1.0						V	Maximum DC Reverse Current, at rated DC Blocking Voltage	10.0						$\mu$ A		1.0						mA	Typical Junction Capacitance per Bridge Element	24.0						PF	Operating Temperature Range ,T <sub>A</sub>	- 65 To + 125						°C	Storage Temperature Range T <sub>STG</sub>	- 65 To + 150						°C
	B40C1500	B80C1500	B125C1500	B250C1500	B380C1500	B500C1500	UNITS																																																																																																		
Maximum Recurrent Peak Reverse Voltage	90	180	350	600	900	1200	V <sub>RRM</sub>																																																																																																		
Maximum RMS Bridge Input Voltage	70	140	280	420	560	700	V <sub>RMS</sub>																																																																																																		
Maximum DC Blocking Voltage	90	180	350	600	900	1000	V <sub>DC</sub>																																																																																																		
Maximum Average Forward Rectified Current 373" (9.5mm) Lead Lengths at T <sub>A</sub> =25°C	1.5						A(AV)																																																																																																		
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC Method)	50						A <sup>2</sup> S																																																																																																		
I <sup>2</sup> t Rating for Fusing (t<.00835ms)	5.0																																																																																																								
Maximum Forward Voltage Drop per Element at 1.0A	1.0						V																																																																																																		
Maximum DC Reverse Current, at rated DC Blocking Voltage	10.0						$\mu$ A																																																																																																		
	1.0						mA																																																																																																		
Typical Junction Capacitance per Bridge Element	24.0						PF																																																																																																		
Operating Temperature Range ,T <sub>A</sub>	- 65 To + 125						°C																																																																																																		
Storage Temperature Range T <sub>STG</sub>	- 65 To + 150						°C																																																																																																		

**NOTES:** 1.-Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

